

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 May 2005 (19.05.2005)

PCT

(10) International Publication Number
WO 2005/045311 A3

(51) International Patent Classification⁷: **H05B 37/02**

(74) Agents: NG, Chun M. et al.; Perkins Coie LLP, Patents-SEA, P.O. Box 1247, Seattle, wa 98111-1247 (US).

(21) International Application Number:
PCT/US2004/035594

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 26 October 2004 (26.10.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/517,306 3 November 2003 (03.11.2003) US

(71) Applicant (*for all designated States except US*): **MONO-LITHIC POWER SYSTEMS, INC.** [US/US]; 983 University Avenue, Building D, Sunnyvale, ca 95032 (US).

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(72) Inventors; and

(75) Inventors/Applicants (*for US only*): **MOYER, James C.** [US/US]; 6381 Wisteria Way, San Jose, CA 95129 (US). **HSING, Michael R.** [US/US]; 19850 Lanark Avenue, Saratoga, CA 95070 (US). **DAVIET, Jean-Francois** [FR/US]; 4312 Grover Drive, Fremont, CA 94536 (US).

Published:
— with international search report

[Continued on next page]

(54) Title: DRIVER FOR LIGHT SOURCE HAVING INTEGRATED PHOTOSENSITIVE ELEMENTS FOR DRIVER CONTROL



(57) Abstract: A method for automatically adjusting the intensity of a lighting element based on feedback from internal and external sources of light is disclosed herein. A photosensitive element senses ambient light and transmits an electrical signal proportional to the intensity of the ambient light to a driver. The driver automatically adjusts the intensity of the lighting element based on this feedback to provide optimal conditions for the application. In addition, the lighting element transmits an electrical signal proportional to the intensity of the light from the lighting element to a driver. The driver further adjusts the intensity of the lighting element based on this feedback to provide optimal conditions for the application.



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(88) **Date of publication of the international search report:**
25 August 2005